____/_

Serial No. 11422

TO APPROPRIATE !	THE	PUBLIC	WATERS	OF	THE STATE	OF	NEVADA

Re	tur	of first receipt and filing in State Engineer's office NOV 7 1945 ned to applicant for correction cted application filed
	,1 T U	
		The undersigned E. H. Thomas & H. W. Polk
of		Name of applicant Las Vegas , County of Clark ,
11.		of Nevada , hereby make application for
₩.	4	ssion to appropriate the public waters of the State of Nevada, as
滙.		nafter stated. (If applicant is a corporation, give date and place
of	iŗ	corporation.)
# :		
ı.	. 1	he source of the proposed appropriation is an underground source Name of stream, lake, or other source
		in Las Vegas Artesian Basin
2.	ָרָי .	he amount of water applied for is 1.00 second-feet.
3.	. 1	he water to be used for Quasi-Municipal purposes
		irrigation, power, mining, manufacturing, domestic, of their use
4.		he water is to be diverted from its source at the following point:
W	<u>ith</u>	in the SE1 NW1 Sec. 28, Twp. 20 South, Range 61 East, MD. B&M. as being within a 40-acre subdivision of public survey, or by course and distance to a section corner. If on unsurveyed land, it should be so stated.
a	t a	point from which the Na cor. of said Sec. 28 bears N 19° 15! E
įa.	dis	stance 2165.0 feet.
* -		IF THE WATER IS TO BE USED FOR IRRIGATION, SUPPLY THE FOLLOWING INFORMATION:
(ε	a) :	Number of acres to be irrigated is
(1))	Description of land to be irrigated
	;	Describe by legal subdivision, or it on this aveyed land to about
	be so	stated and a description provided in accordance with special instruction from the State Engineer when application is returned for correction.
-		
	- ,	
	- 7	
((;)	Use will begin about $\frac{\text{Jan.lst}}{\text{Month}}$ and end about $\frac{\text{Dec.3lst}}{\text{Month}}$, of each year.
	I	F WATER IS TO BE USED FOR POWER, MINING, STOCK WATERING, OR OTHER USE, SUPPLY THE
		FOLLOWING INFORMATION:
[[(c	1)	Power to be developed is horsepower.
(⊖)	Place of use same subdivision as the point of diversion. Give location of place of use by legal subdivision.
	. <i>' _j '</i>	Deint of moture of woton to stream
[]	P)	Point of return of water to stream Describe in same manner as point of diversion.
(ફ	3)	State number and kinds of animals to be watered
(1	1)	Use will begin about and end about, of each year.
11 (i.)	Remarks A subdivision is being presently prepared for this
		40 acre parcel, all preliminary work completed.
-		

DESCRIPTION OF PROPOSED WORKS

17.	of the subdivision				 :	
1		. , , , , , , , , , , , , , , , , , , ,				
	Estimated cost of works	\$3000.00				<u>'</u>
	Estimated time required to		one vear		·	
•						de cita de acto
•	Remarks	For use of applicant				
1	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·		<u> </u>	<u>.</u> .	
1						
	E. H. Thomas			er ar septembre		
1.	H. W. Polk	, Applicant.				
1.		By <u>Jack A</u> State Wate	sher r-Right Surve	vor	- ;	
ņ	pared BB-AT			ing Park		
hi	s sheet inspected			ر . در اسمار سور کنونجیس		
1		, Engineer.		T. Contract		
	A DDE	ROVAL OF STATE ENGI	NEER	714		
			•	3		
	This is to certify that I				1,	,
nd	do hereby grant the same,	subject to the foll	lowing limitat	ions and	. !	
on	ditions: This permit is iss	sued subject to al	5	a on the	anning	
1	. A valve must be in	estalled and maint	r prior rig n t	ent weste	source	•
at	A valve must be in er. A meter must be instal	nstalled and maint Lled in the pipe l	ained to prev ine, near the	ent waste point of	_of diver	
ol ai:	A valve must be instaler. A meter must be instaled that accurate measurements ned. This source is located	nstalled and maint lled in the pipe l of water placed t ed within an area	ained to previne, near the obeneficial that has been	ent waste point of use may b designat	_of diver e ob- ed by	si
ol ai La	A valve must be instaler. A meter must be instaled that accurate measurements ned. This source is located to Engineer as coming within	nstalled and maint lled in the pipe l of water placed t ed within an area in the meaning of	ained to previne, near the obeneficial that has been the provision	ent waste point of use may b designat s of the	_of diver e ob- ed by 1 939	si th
ol ai ta nd	A valve must be instaler. A meter must be instaled that accurate measurements ned. This source is located	nstalled and maint led in the pipe l of water placed t ed within an area in the meaning of ided in 1943; the	ained to previne, near the obeneficial that has been the provision refore the St	ent waste point of use may b designat s of the ate reser	_of diver e ob. ed by 1939 ves th	si th
ol ai. ai nd	A valve must be instaler. A meter must be instaled that accurate measurements ned. This source is located to Engineer as coming withing erground Water Act, as amental to regulate the use of the source of the sour	nstalled and maint led in the pipe led of water placed to ed within an area of the meaning of the water herein grants.	ained to previne, near the obeneficial that has been the provision refore the Stranted at any	ent waste point of use may b designat s of the ate reser and all	_of diver e ob. ed by 1939 ves th	si th
nd g	A valve must be instaler. A meter must be instaled that accurate measurements ned. This source is located to Engineer as coming within erground Water Act, as amend to regulate the use of the amount of water to be approximately amount of water to	nstalled and maint led in the pipe led of water placed to ded within an area of the meaning of the water hereing opriated shall be in the meaning of the water hereing opriated shall be in the meaning of the water hereing opriated shall be in the meaning opriated s	ained to prewine, near the obeneficial that has been the provision refore the Stranted at any limited to the	ent waste point of use may b designat s of the ate reser and all amount	_of diver e ob. ed by 1939 ves th	si th
nd g	A valve must be instaler. A meter must be instaled that accurate measurements ned. This source is located to Engineer as coming withing erground Water Act, as amental to regulate the use of the source of the sour	nstalled and maint led in the pipe led of water placed to ded within an area of the meaning of the water hereing opriated shall be in the meaning of the water hereing opriated shall be in the meaning of the water hereing opriated shall be in the meaning opriated s	ained to prewine, near the obeneficial that has been the provision refore the Stranted at any limited to the	ent waste point of use may b designat s of the ate reser and all amount	_of diver e ob. ed by 1939 ves th	si th
ne ni	A valve must be instaler. A meter must be instaled that accurate measurements ned. This source is located to Engineer as coming within erground Water Act, as amend to regulate the use of the amount of water to be approximately amount of water to	nstalled and maint led in the pipe led of water placed to ed within an area in the meaning of ided in 1943; the water herein greated shall be lead use, and not to the lead of	ained to prewine, near the obeneficial that has been the provision refore the Stranted at any limited to the control of the co	ent waste point of use may b designat s of the ate reser and all amount	_of diver e ob. ed by 1939 ves th	si th
ni di	A valve must be instal er. A meter must be instal that accurate measurements ned. This source is located to Engineer as coming within erground Water Act, as amend to regulate the use of the amount of water to be approach can be applied to benefic	nstalled and maint led in the pipe led within an area of the meaning of ided in 1943; the he water hereing opriated shall be a sial use, and not to exceed 150,000 and to exceed 150,000 and to exceed 150,000 and to the water hereing the shall be a sial use, and not the exceed 150,000 and the exceed	ained to prewine, near the obeneficial that has been the provision refore the Stranted at any limited to the scaled of the gallons per d	ent waste point of use may b designat s of the ate reser and all amount 0 c.f.s.	_of diver e ob. ed by 1939 ves th	si th
deli	A valve must be instaler. A meter must be instaled that accurate measurements ned. This source is located to Engineer as coming within erground Water Act, as amended to regulate the use of the amount of water to be approached to benefice in the contract of the contract	stalled and maint led in the pipe I of water placed to ded within an area of the meaning of ded in 1943; the he water hereing opriated shall be in the meaning of the water hereing opriated shall be in the control of	ained to prewine, near the obeneficial that has been the provision refore the Stranted at any limited to the gallons per decent of the control of the contro	ent waste point of use may b designat s of the ate reser and all amount 0 c.f.s.	_of diver e ob. ed by 1939 ves th	si th
id and in the state of the stat	A valve must be instaler. A meter must be instaled that accurate measurements ned. This source is located to Engineer as coming within erground Water Act, as amend to regulate the use of the amount of water to be approached an be applied to beneficial text as a manual construction work shall	stalled and maint led in the pipe I of water placed to ded within an area on the meaning of ided in 1943; the opriated shall be I to exceed 150,000 and begin on or before shall be filed before the sha	ained to prewine, near the obeneficial that has been the provision refore the Stranted at any limited to the gallons per decorate Nov. 10.	ent waste point of use may b designat s of the ate reser and all amount 0 c.f.s. 1946	of diver ed ob.	si th
ne ni do r	er. A meter must be instalthat accurate measurements ned. This source is located to Engineer as coming within erground Water Act, as amended to regulate the use of the amount of water to be approached to benefice increase type and the construction work shall of of commencement of work and the construction of work and the construction work shall of of commencement of work and the construction work and the	stalled and maint led in the pipe I of water placed to ded within an area on the meaning of ided in 1943; the opriated shall be I to exceed 150,000 and begin on or before shall be filed before the sha	ained to prewine, near the obeneficial that has been the provision refore the Stranted at any limited to the gallons per decorate Nov. 10.	ent waste point of use may b designat s of the ate reser and all amount 0 c.f.s. 1946	of diver ed ob.	si th
i de li do ref	A valve must be instaler. A meter must be instaled. This source is located to Engineer as coming within erground Water Act, as amended to regulate the use of the amount of water to be approached to benefice instance. The property of the construction work shall of of commencement of work shall or or commencement of work shall or or commencement of work shall or construction.	stalled and maint led in the pipe I of water placed to ded within an area in the meaning of ided in 1943; the he water herein group opriated shall be I co exceed 150,000 group begin on or before shall be filed before asonable diligence	ained to prewine, near the obeneficial that has been the provision refore the Stranted at any limited to the control of the co	ent waste point of use may b designat s of the ate reser and all amount 0 c.f.s. 1946 eted on o	of diver ed ob.	si th
in a de la contra del la contra de la contra de la contra del la contra del la contra del la contra de la contra del	A valve must be instaler. A meter must be instaled that accurate measurements ned. This source is located to Engineer as coming within erground Water Act, as amended to regulate the use of the can be applied to benefice in the construction work shall of of commencement of work sk must be prosecuted with respect to the completion of work shall of of completion of work shall of the completion of w	stalled and maint led in the pipe I of water placed to ded within an area in the meaning of ided in 1943; the she water herein group opriated shall be in the case of the case	ained to prewine, near the obeneficial that has been the provision refore the Stranted at any limited to the control of the second of the limited to the second of the limited to the limited limite	ent waste point of use may b designat s of the ate reser and all amount 0 c.f.s. 1946 eted on o	of diver ed ob.	si th
nd de ni cor	A valve must be instaler. A meter must be instaled that accurate measurements ned. This source is located to Engineer as coming within erground Water Act, as amended to regulate the use of the amount of water to be approached to benefice in the engineer as coming within the can be applied to benefice in the engineer as coming within the engineer as coming within the engineer as coming within the engineer and th	stalled and maint led in the pipe I of water placed to ded within an area in the meaning of ided in 1943; the she water herein group opriated shall be in the case of the case	ained to prewine, near the obeneficial that has been the provision refore the Stranted at any limited to the coexceed 0.5 gallons per decorpt of Nov. 10. and be completed on or being and on or being and the complete on the complete	ent waste point of use may b designat s of the ate reser and all amount 0 c.f.s. 1946 1946 eted on o	of ver ed oby the ed of ver et of the ed of th	si th
nd db ct ro	A valve must be instaler. A meter must be instaled that accurate measurements ned. This source is located to Engineer as coming within erground Water Act, as amended to regulate the use of the can be applied to benefice in the construction work shall of of commencement of work sk must be prosecuted with respect to the completion of work shall of of completion of work shall of the completion of w	stalled and maint led in the pipe I of water placed to ded within an area in the meaning of ided in 1943; the she water herein group opriated shall be in the case of the case	ained to prewine, near the obeneficial that has been the provision refore the Stranted at any limited to the coexceed 0.5 gallons per decorpt of Nov. 10. and be completed on or being and on or being and the complete on the complete	ent waste point of use may b designat s of the ate reser and all amount 0 c.f.s. 1946 1946 eted on o	of ver ed oby the ed of ver et of the ed of th	si th
ne ni ne ro	A valve must be interested er. A meter must be installed that accurate measurements ned. This source is located the Engineer as coming within erground Water Act, as amended to regulate the use of the amount of water to be approached to benefice increase the engineer as coming within the construction work shall of of commencement of work shall of of commencement of work shall or oreOct. 10, 1947 of of completion of work shall ication of water to beneficeOct. 10, 1948 Oct. 10, 1948 Proof	istalled and maint led in the pipe I of water placed to ded within an area in the meaning of ided in 1943; the she water herein group opriated shall be in the case of the filed before the shall be filed before the case all be filed before the case all be filed before the application of the application	ained to prewine, near the obeneficial that has been the provision refore the Stranted at any limited to the coexceed 0.5 gallons per decorated and be completed and be completed to the nor water to	ent waste point of use may b designat s of the ate reser and all amount 0 c.f.s. 1946 eted on o 1947 core beneficia	of vere ed oby the ed of vere ed of vere ed of the ed of	si th
he hi o r f o p	A valve must be instaler. A meter must be instaled that accurate measurements ned. This source is located the Engineer as coming within erground Water Act, as amend to regulate the use of the to regulate the use of the can be applied to benefice in the construction work shall of of commencement of work shall of of commencement of work shall of of completion of work shall oct. 10, 1947 Oct. 10, 1948 Proof	stalled and maint led in the pipe I of water placed to ded within an area in the meaning of ided in 1943; the she water herein group opriated shall be in the case of the filed before that I be filed before the filed before that I be filed before the filed before that I be filed before the file	ained to prewine, near the obeneficial that has been the provision refore the Stranted at any limited to the coexceed 0.5 gallons per decorated and be completed and be completed to the nor water to	ent waste point of use may b designat s of the ate reser and all amount 0 c.f.s. 1946 eted on o 1947 core beneficia	of vere ed oby the ed of vere ed of vere ed of the ed of	si th
he hi o r f o p	A valve must be instaler. A meter must be instaled that accurate measurements ned. This source is located to Engineer as coming within erground Water Act, as amended to regulate the use of the amount of water to be approached to benefice in the engineer as coming within the can be applied to benefice in the engineer as coming within the engineer as coming within the engineer as coming within the engineer and th	istalled and maint led in the pipe I of water placed to ded within an area in the meaning of ided in 1943; the she water herein group opriated shall be in the case of the filed before the application in	ained to prewine, near the obeneficial that has been the provision refore the Stranted at any limited to the coexceed 0.5 gallons per decorpt of Nov. 10. and be completed in of water to the Nov. 10. The Nov. 11. T	ent waste point of use may b designat s of the ate reser and all amount 0 c.f.s. 1946 eted on o 1947 core beneficia	of vere ed oby the ed of vere ed of vere ed of the ed of	si th
he hi do r o r o p e e i	er. A meter must be instal that accurate measurements ned. This source is located the Engineer as coming within erground water Act, as amen to regulate the use of the amount of water to be approached to benefic the first that the second water are to be approached to benefic the first that the second water to be approached to a second water to be approached with se	stalled and maint led in the pipe I of water placed to ded within an area in the meaning of ided in 1943; the she water herein group opriated shall be in the case of the filed before that I be filed before the filed before that I be filed before the filed before that I be filed before the file	ained to prewine, near the obeneficial that has been the provision refore the Stranted at any limited to the coexceed 0.5 gallons per decorpt of Nov. 10. and be completed in of water to the Nov. 10. The Nov. 11. T	ent waste point of use may b designat s of the ate reser and all amount 0 c.f.s. 1946 eted on o 1947 core beneficia	of vere ed oby the ed of vere ed of vere ed of the ed of	si th
he hi do r o r o p e e i	A valve must be instaler. A meter must be instaled that accurate measurements ned. This source is located the Engineer as coming within erground Water Act, as amend to regulate the use of the to regulate the use of the can be applied to benefice in the construction work shall of of commencement of work shall of of commencement of work shall of of completion of work shall oct. 10, 1947 Oct. 10, 1948 Proof	istalled and maint led in the pipe I of water placed to ded within an area in the meaning of ided in 1943; the she water herein group opriated shall be in the case of the filed before the application in	ained to prewine, near the obeneficial that has been the provision refore the Stranted at any limited to the coexceed 0.5 gallons per decorpt of Nov. 10. and be completed in of water to the Nov. 10. The Nov. 11. T	ent waste point of use may b designat s of the ate reser and all amount 0 c.f.s. 1946 eted on o 1947 core beneficia	of vere ed oby the ed of vere ed of vere ed of the ed of	si th